



Collezioni
Sale & Pepe
12-9-7 mm

RB
CERAMICHE
MADE ITALY



32,5x32,5 Sale & Pepe Avana



** Pavimento 30,5x61 a richiesta

DATI TECNICI <i>technical data</i>	FORMATO <i>size</i>		PCS/BOX	M /BOX	KG/BOX	BOX/PLT	M/PLT	KG/PLT	PLT/M CNTR 20	EURO/MQ
PAVIMENTO	32,5X32,5	12 mm	9	0,95	23,60	69	65,55	1628	17/1114,35mq	26,00
PAVIMENTO	32,5X32,5	9 mm	13	1,38	22,75	69	95,22	1590	17/1618,74mq	20,00
PAVIMENTO	32,5X32,5	7 mm	16	1,69	20,50	69	116,61	1435	19/2215,59mq	19,00
PAVIMENTO **	30,5X61	8,2 mm	8	1,49	23,60	60	89,40	1440	19/1698,60mq	22,00

R10 Interno & Esterni



- 4530 32,5X32,5 BEIGE R10 7mm
- 4540 32,5X32,5 BEIGE R10 9mm
- 4550 32,5X32,5 BEIGE R10 12mm



- 4531 32,5X32,5 AVANA R10 7mm
- 4541 32,5X32,5 AVANA R10 9mm
- 4551 32,5X32,5 AVANA R10 12mm



- 4532 32,5X32,5 GREY R10 7mm
- 4542 32,5X32,5 GREY R10 9mm
- 4552 32,5X32,5 GREY R10 12mm



- 4533 32,5X32,5 DARK R10 7mm
- 4543 32,5X32,5 DARK R10 9mm
- 4553 32,5X32,5 DARK R10 12mm

R11 Interno & Esterni Anti Slip



- 4535 32,5X32,5 BEIGE R11 7mm
- 4545 32,5X32,5 BEIGE R11 9mm
- 4555 32,5X32,5 BEIGE R11 12mm



- 4536 32,5X32,5 AVANA R11 7mm
- 4546 32,5X32,5 AVANA R11 9mm
- 4556 32,5X32,5 AVANA R11 12mm



- 4537 32,5X32,5 GREY R11 7mm
- 4547 32,5X32,5 GREY R11 9mm
- 4557 32,5X32,5 GREY R11 12mm



- 4538 32,5X32,5 DARK R11 7mm
- 4548 32,5X32,5 DARK R11 9mm
- 4558 32,5X32,5 DARK R11 12mm



GRES PORCELLANATO PORFIRIZZATO

Caratteristiche Tecniche

Unglasiertes Feinsteinzeug - Unglazed Porcelain Floor Tiles - Grès Cérame Protégé
Technische Anforderungen - Technical Characteristics - Caractéristiques Techniques
UNI EN 14411 B1a UGL

	Valori Prescritti International Normwerte International Standards Valeurs	RB Valori Medi RB Mittelwerte RB Average Values RB Valeurs Moyens	NORMA Norme Norm Regulation
Lunghezza e Larghezza Laenge und Breite der Fliesen Length and Width Longueur et Largeur	± 0,6 %	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-2
Spessore Staerke Thickness Epaisseur	± 5,0 %	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-2
Rettilineità degli Spigoli Geradlinigkeit Straightness Equerrage des Angles	± 0,5%	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-2
Assorbimento d'Acqua Wasseraufnahme Water Absorption Absorption d'Eau	< 0,5%	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-3
Resistenza alla Flessione Biegefestigkeit Breaking Strength Résistance à la Flexion	> 27 N/mm ²	> 35 N/mm ²	UNI EN ISO 10545-4
Resistenza agli Stalzi Termici Temperaturwechsel - Bestaendigkeit Thermal Shock Resistance Résistance aux Ecartis Thermiques	Nessun Danno Kein Schaden No Damage Aucun Dommage	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-9
Resistenza al Gelo Frostbestaendigkeit Frost Resistance Résistance au Gel	Nessun Danno Kein Schaden No Damage Aucun Dommage	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-12
Resistenza all'Attacco Chimico Saeure - Laugebestaendigkeit Chemical Resistance Résistance à l'Attaque Chimique	Nessun Danno Kein Schaden No Damage Aucun Dommage	Conforme Entsprechend In Accordance Conforme	UNI EN ISO 10545-13
Schivolosità Rutschemmende Eigenschaft Skid Resistance Nature Glissante	> 9	> 9	DIN 51130



ITALY

RB S.r.l.

41053 Maranello (MO) Italy - Via Vignola, 11 - P.IVA e C.F. 03628420360

export@rbceramiche.com

info@rbceramiche.com www.rbceramiche.com