

Collezioni TROPEA



serie Tropea



60x60 Tropea Onice



4850 60x60 Tropea Bianco



4851 60x60 Tropea Grey



4852 60x60 Tropea Grigio

serie Tropea



4853 60x60 Tropea Ivory



4854 60x60 Tropea Beige



4855 60x60 Tropea Avorio



4856 60x60 Tropea Ocra



4857 60x60 Tropea Rosa



4858 60x60 Tropea Avana



4859 60x60 Tropea Bronzo




4860 60x60 Tropea Oro



4861 60x60 Tropea Onice

Contanier pallet n.23 mq.1324,80

DATI TECNICI <i>technical data</i>	FORMATO <i>size</i>		PCS/BOX	M /BOX	KG/BOX	BOX/PLT	M /PLT	KG/PLT		EURO/MQ
<i>gres porcellanato dig.</i>	60x60	9,5 mm	4	1,440	31	40	57,60	1260		25,00

TECHNICAL SPECIFICATION

Sr.No	Particulars	STANDARD as per ISO 13006/EN 176 Group Bla	OUR VALUE	Method OF TESTING
1	Deviation In Length	± 0.60%	± 0.10%	ISO 10545 - 2
2	Deviation In Thickness	± 5%	± 2%	ISO 10545 - 2
3	Straightness Of Sides	± 0.50%	± 0.10%	ISO 10545 - 2
4	Rectangularity	± 0.60%	± 0.20%	ISO 10545 - 2
5	Surface Flatness	± 0.50%	± 0.20%	ISO 10545 - 2
6	Water Absorption*	< 0.05%	<0.05%	ISO 10545 - 2
7	Mohs Hardness*	< 6	< 7	EN 101
8	Flexural Straightness*	> 35 N/MM ²	> 45 N/MM ²	ISO 10545 - 4
9	Abrasion Resistance	> 175MM ³	> 144 MM ³	ISO 10545 - 6
10	Skid Resistance	> 0.4	< 0.4	ISO 10545 - 17
11	Breaking Strength*	1113 N	2500 N	ISO 10545 - 4
12	Density(g/cc)	> 2	2.4	ISO 10545 - 4
13	Frost Resistance	Frost Proof	Frost Proof	ISO 10545 - 12
14	Chemical Resistance	No Damage	No Damage	ISO 10545 - 13
15	Thermal Shock Resistance	No Damage	No Damage	ISO 10545 - 9
16	Colour Resistance	No Damage	No Damage	DIN 51094
17	Thermal Expansion	< 9x10-6	< 6x10-6	ISO 10545 - 8
18	Stain Resistance	Resistant	Resistant	DIN 51094
19	Moisture Expansion	Nil	Nil	DIN 51094
20	Glossiness	-	> 65% reflection	Gloss Meter



RB S.r.l.

41053 Maranello (MO) Italy - Via Vignola, 11 - P.IVA e C.F. 03628420360

info@rbceramiche.com www.rbceramiche.com

export@rbceramiche.com